

PROVIDING A SOLUTION FOR EVERY GLASS DISPLAY DOOR APPLICATION



	Normal Temp					Low Temp		
	Select	Pro-E	Prime	Vue	Everest	Select	Pro-E	Everest
Application								
Cooler		☑	☑	☑	☑			
Freezer						☑	☑	☑
Heavy-Duty Beer Cave	☑	☑						
Temperature/Environment								
Normal Temp: 75°F/ 60% RH Ambient/35°F Walk-In	☑		☑	☑				
High Humidity: 75°F/ 65% RH Ambient/35°F Walk-In	Optional (65%)	☑			☑			
Low Temp: 75°F/ 55% RH Ambient/ -10°F Walk-In						☑		
Low Temp: 75°F/ 65% RH Ambient/ -10°F Walk-In		☑			☑		☑	☑
Glass Pack Configuration								
Glass Standard – 3-pane		☑			☑	☑	☑	☑
Glass Standard – 2-pane	☑		☑	☑				
All-Glass Look			☑		☑			☑
Standard Package								
Magnetic Door Gaskets	☑	☑			☑	☑	☑	☑
Aircell PVC Gasket			☑	☑				
Automatic Hold-Open & Door Stop	☑	☑	☑	☑		☑	☑	☑
Hinge Pin	☑	☑	☑	☑	☑	☑	☑	☑
Torque & Sag Adjust	☑	☑	☑	☑	☑	☑	☑	☑
Reversible Door	☑	☑			☑	☑	☑	☑
Door Handle	Standard Metal	Standard Metal	Elliptical	Elliptical	Standard Metal	Standard Metal	Standard Metal	Standard Metal
Full-Length Handle	Optional	Optional			Optional	Optional	Optional	Optional
Lighting Options								
No Lighting	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Eco LED	☑	☑				☑	☑	
EnVision	Optional	Optional	Standard Swing	Standard Swing		Optional	Optional	
EnVision FD (French Door) no Horizontal			French Swing	French Swing				
EnVision FD (French Door) with Horizontal		Optional	Optional	Optional				
Swing Availability								
Standard L/R	☑	☑	☑	☑	☑	☑	☑	☑
French Swing without Mullion	☑	☑	☑	☑	☑			☑
Heat Settings								
Door Rail Heat	No	No	No	No	No	Yes	Yes	No
Pass-thru option								
Matching Pass-Thru Door	☑	☑			☑			☑
Optional Glass (1/3 Glass with 2/3 Block out Panel)	☑	☑						
Kickplates (10", 24", 36", and 48")	☑	☑						
Energy Consumption								
Normal Temperature – Heated Frame	1.21 kWh/day	1.21 kWh/day	1.21 kWh/day	1.21 kWh/day	1.21 kWh/day			
Normal Temperature – French Door – Heated Frame	.79 kWh/day	.79 kWh/day	.79 kWh/day	.79 kWh/day	.79 kWh/day			
Low Temperature						3.2 kWh/day	3.2 kWh/day	3.2 kWh/day

* Energy consumption values listed are actual values and are based on a catalog size 30" x 75", 4 door line up for each model. These doors are designed and certified for use in walk-in cooler and/or walk-in freezer applications.



GET IN TOUCH! Please call or contact our sales department today.



ENERGY DOOR COMPANY

180 Arboit Street, L'Assomption, Quebec J5W 4P5

energydoorco.com | 844 433 0332 | sales@energydoorco.com

PROVIDING A SOLUTION FOR EVERY GLASS DISPLAY DOOR APPLICATION

