



SELECT™ PASS-THROUGH

Simple, Durable Door System

A RELIABLE AND DURABLE WORKHORSE

The SELECT™ door system is engineered with superior energy-efficiency and offers an attractive low maintenance design for the energy-conscious retailer. Increase product visibility and boost sales with a system that provides trouble-free performance for years to come. The SELECT™ door system offers high impact metal handles, dual seal insulated glass and many more attractive features.

SPECIFICATIONS



Door Sizes:

Width: 30"

Height: 75", 79"

Performance:

Normal Temp - 75F/60%

Shelving:*

30", 60"

Deep Shelving:

24", 27", 36", 42"

Optional Shelving: Gravity Flow, Flex Carts, MiniRoller™

Finishes: Black, Silver Satin, Polished Aluminum

*5 shelves STD, 7 shelves on 79", Standard Black and White

WARRANTY

✓ **10 Year** Sealed Glass Unit

✓ **5 Year** LED

✓ **1 Year** Workmanship and Labor





LIGHTING SPECIFICATIONS

		EcoLED2	EnVision2	EnVisionFD
Electrical		24V	24V	24V
Color Temperature (CCT)		4000K	4000K	3500K/4000K
Lumen Maintenance		L70-180,000hrs	L90-100,000hrs	L70 180,000hrs
Lengths/Wattage		60" - 9.5W	70" - C 12.5W - L/R 6W	70" - 23.5W (other sizes available)
Light Performance	Efficacy	70" - 11W	110 lm/W	130 lm/W
	CRI	85	95	85
	Lumens	70" - 1425	70" - C 1875 - L/R 500	70" - 3050
Certification		UL, UL2108, CE, DLC 5.1 listed, ANSI 2/NSF, EN60335-2-24		
		IP54, IK08	IK10, IP66	IP54, IK08

**Other types of LED available upon request*



FEATURES

- Metal handle
- Push bar
- High-performance 2-pane glass
- Full flange
- Standard or French swing configuration
- Torque master tension adjustment
- Dual seal insulated glass
- Energy controller



AVAILABLE OPTIONS

- Envision™ LED lighting
- Locks available
- MiniRoller
- Flex carts
- Full-length handle
- Kick plates



GET IN TOUCH! Please call or contact our sales department today.

