

## VISUALLY RICH AND VIBRANT LIGHTING

- Market leading 130 lm/W efficiency, with high color rendering spectrum technology.
- Highest achievable impact resistance, of IK10
- Provides premium color performance, delivering 95CRI. Today, using the latest industry color quality standard TM-30 metrics, it achieves near perfect color tones and accuracy across the entire color spectrum Rg 99.75 and Rf 95.
- Superior optical uniformity vs all leading competitors.
- Application specific optical beam control.
- Smallest profile vertical application refrigeration lighting product on the market.





















## **SPECIFICATIONS**

Power (W)	3 - 15
Output (Im)	400 - 1950
Efficacy (lm/W)	up to 130
Color Temperatures	3500K, 4000K, 5000K
CRI (Ra)	95
SDCM	3
Operating Temp. (°F)	-22 to +95
Materials	Aluminum / Polycarbonate



EnVision 2 (95 CRI)



20



EnVision 2 FD is standard with french door applications, with an optional horizontal fixture.





## **FEATURES**

Fully compliant with DOE 2017 regulations

**DELIVERS HIGH COLOR RENDERING INDEX (CRI)** 

**EVEN LIGHT DISTRIBUTION** 

HIDDEN LIGHT SOURCE THAT PROVIDES ULTIMATE SHOPPING EXPERIENCE

**REDUCES MAINTENANCE COST** 

MEDIUM AND LOW TEMPERATURE APPLICATIONS

## **AVAILABLE OPTIONS**

SINGLE DOOR

**FRENCH DOOR** 

**HORIZONTAL LIGHTING** 

COLOR TEMPERATURES: 3500K, 4000K AND 5000K

3', 4', 5', 6' LENGTHS AVAILABLE