

ENERGY CONSUMPTION SAVINGS

Increase performance and reduce your energy cost with the smart design PRO-E™ door system. Triple pane/dual seal insulated glass provides you the best performance and energy consumption savings with unparalleled condensation protection. Even in the most demanding conditions the PRO-E™ door model is durable and energy-efficient which equates to the lowest cost of ownership.

WARRANTY





10 Year Sealed Glass Unit 0 5 Year LED 0 1 Year Workmanship and Labor







FOR MORE INFO

SPECIFICATIONS



Door Sizes (Custom Sizes Available)	24"	26"	28"	30" Width
	67"	75"	79"	Height

Shelving* (Standard Black and White) *5 shelves STD, 7 shelves on 79"

| 24" | 26" | 28" | 30" | 48" | 52" | 56" | 60" |

Deep Shelving | 24" | 27" | 36" | 43" |

Optional Shelving | Gravity Flow | Flex Carts" |

Normal Temp - 75F/35F/65% | Low Temp - 75F/-10F/60% Performance:



		EcoLED2	EnVision2	EnVisionFD	
Electrical		24V	24V	24V	
Color Temperature (CCT)		4000K	3500K/4000K	3500K/4000K/5000K	
Lumen Maintenance		L70-180,000hrs L90-54,000hrs	L70 178,000hrs L90-54,000hrs	L70 180,000hrs L90-54,000hrs	
Lengths/Wattage		60"- 9.5W	60"- C 10W - L/R 5W	60"- 19.5W 66"- 21.5W	
		70"- 11W	70"- C 12.5W - L/R 6W	70"- 23.5W	
Light Performance Effic		130 lm/W	110 lm/W	130 lm/W	
	CRI	84	95	84	
	Lumens	60"- 1235	60"- C 1100 - L/R 550	60"- 2535 66"- 2795	
		70"- 1430	70"- C 1375 - L/R 660	70"- 3055	
Certification		UL, UL2108, CE, DLC 5.1 listed, ANSI 2/NSF, EN60335-2-24			
		IP54, IK08	IP64, IK10	IP54, IK08	

FEATURES

Fully compliant with DOE 2017 regulations







AVAILABLE OPTIONS







ENVISION™ LED LIGHTING

ENERGY FREE FRAME

DUAL, AFTERMARKET AND CYLINDER LOCKS AVAILABLE

FINISHES: BLACK | SILVER SATIN

ANTI-FOG COATING

HORIZONTAL LED LIGHTING (FRENCH DOOR ONLY)

GRAVITY FLOW SHELVING

DOUBLE-WIDE SHELVING FOR FRENCH DOORS

FLEX CARTS

MATCHING PASS-THRU SINGLE AND DOUBLE-ENTRY DOORS

STANDARD LED LIGHTING

STANDARD OR FULL-LENGTH HANDLE AVAILABLE

HIGH-PERFORMANCE 3-PANE GLASS

MAGNETIC GASKET

FIELD REVERSIBLE

CONTINUOUS OR FULL FLANGE

STANDARD OR FRENCH SWING CONFIGURATION

90 DEGREE HOLD OPEN

TORQUE MASTER TENSION ADJUSTMENT

DUAL SEAL INSULATED GLASS

ENERGY CONTROLLER