

HIGH HUMIDITY, DURABLE, AND ENERGY EFFICIENT

Increase performance and reduce your energy cost with the smart design PRO-E[™] door system. Triple pane/dual seal insulated glass provides you the best performance and energy consumption savings with unparalleled condensation protection. Even in the most demanding conditions the PRO-E[™] door model is durable and energy-efficiency which equates to the lowest cost of ownership.

WARRANTY



🜔 10 Year Sealed Glass Unit 🛛 🜔 1 Year Workmanship and Labor





High Humidity, Durable Door System



70"- C 1375 - L/R 660

UL, UL2108, CE, DLC 5.1 listed, ANSI 2/NSF, EN60335-2-24

IP64, IK10



	Door Sizes (Custom Sizes Ava	ilable)	30" 36" Width 81" 84" Height		
	Optional Shelving		Flex Carts		
	Performance:		Normal Temp - 75F/65% 3-Pane		
OPTIONAL LIGHTIN	*For ADA compliant order minim	um 36" wid	e & 84" tall EcoLED2		EnVision2
	Electrical		24V		24V
	Color Temperature (CCT)		4000K		3500K/4000K
	Lumen Maintenance		L70-180,000hrs L90-54,000hrs		L70 178,000hrs L90-54,000hrS
	Lengths/Wattage		60"- 9.5W		60"- C 10W - L/R 5W
			70"- 11W		70"- C 12.5W - L/R 6W
	Light Performance	Efficacy	130 lm/W		110 lm/W
		CRI	84		95
Z		Lumens	60"- 1235		60"- C 1100 - L/R 550

70"- 1430

IP54, IK08

SPECIFICATIONS

Certification



ENERGY CONTROLLER

GET IN TOUCH! Please call or contact our sales department today.

180 Arboit Street, L'Assomption, Quebec J5W 4P5 | energydoorco.com | 844 433 0332 | sales@energydoorco.com