

Simple, Durable Door System

# RELIABLE, DURABLE AND A BONA FIDE WORKHORSE

The SELECT™ door system is engineered with superior energy-efficiency and offers an attractive low maintenance design for the energy-conscious retailer. Increase product visibility and boost sales with a system that provides trouble-free performance for years to come. The SELECT™ door system offers high impact metal handles, dual seal insulated glass and many more attractive features.

## **WARRANTY**





10 Year Sealed Glass Unit 12 1 Year Workmanship and Labor











### **SPECIFICATIONS**

Door Sizes (Custom Sizes Available) | 30" | 36" | 38" | Width

| 81" | 84" | Height

Optional Shelving Flex Carts

Performance: Normal Temp - 75F/60%

\*For ADA compliant order minimum 36" wide & 84" tall

		EcoLED2	EnVision2	EnVisionFD
Electrical		24V	24V	24V
Color Temperature (CCT)		4000K	3500K/4000K	3500K/4000K/5000K
Lumen Maintenance		L70-180,000hrs   L90-54,000hrs	L70 178,000hrs   L90-54,000hrs	L70 180,000hrs   L90-54,000hrs
Lengths/Wattage		60"- 9.5W	60"- C 10W - L/R 5W	60"- 19.5W   66"- 21.5W
		70"- 11W	70"- C 12.5W - L/R 6W	70"- 23.5W
Light Performance	Efficacy	130 lm/W	110 lm/W	130 lm/W
	CRI	84	95	84
	Lumens	60"- 1235	60"- C 1100 - L/R 550	60"- 2535   66"- 2795
		70"- 1430	70"- C 1375 - L/R 660	70"- 3055
Certification		UL, UL2108, CE, DLC 5.1 listed, ANSI 2/NSF, EN60335-2-24		
		IP54, IK08	IP64, IK10	IP54, IK08

#### **FEATURES**

Fully compliant with DOE 2017 regulations







## **AVAILABLE OPTIONS**





METAL HANDLE

**PUSH BAR** 

HIGH-PERFORMANCE 2-PANE GLASS

FULL-FLANGE

STANDARD OR FRENCH SWING CONFIGURATION

**HEAVY-DUTY SPRING-LOADED HINGES** 

**DUAL SEAL INSULATED GLASS** 

**ENERGY CONTROLLER** 

ECOLED OR ENVISION™ 2 LIGHTING

FULL-LENGTH HANDLE

**KICK PLATES** 

CYLINDER LOCKS AVAILABLE

FINISHES: BLACK | SILVER SATIN

**FLEX CARTS**